

The Pro's Choice Since 1936

SAKRETE®

Light Weight Mix

For repair and building jobs where concrete thickness exceeds 2 inches (50 mm). Use for pouring footings, setting posts and poles, building walkways, driveways, patios and steps.

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. **WARNING:** Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

DIRECTIONS:

1. Add clean water and mix thoroughly. A stiff batter-like mix is normal. Too much water will weaken the mix.
2. Level by moving a straight edge board back and forth across the fresh concrete.
3. After concrete is firm, use a steel trowel to get a smooth surface or a wood float for a rough surface.

For a non-slip texture, sweep lightly with a broom or brush.

4. To aid curing, spray surface lightly with water 2 or 3 times per day for 3 days.

CURING:

Curing means maintaining proper moisture and temperature. Account for local environmental conditions when selecting the curing method. High heat, low humidity or wind will increase the evaporation of water. Keep the surface damp, using a sprinkler, wet burlap, Sakrete Cure 'N Seal or cover with plastic for several days as needed. In cold weather adequately cover and keep from freezing for a minimum of 24 hours. Refer to ACI 308.

STORAGE:

Store in a tightly closed container off the floor in a dry place.

PACKAGING:

2/3 cu ft. - UPC: 7-64661-14465-6



EAGLE FENCE
★ DISTRIBUTING LLC ★
efdistribution.com

ENVIRONMENTAL ADVISORY:

Uncured or crushed cured cement is an environmental hazard, which may adversely affect fish and wildlife. Dispose of construction debris containing cement, including empty bags, at a permitted municipal disposal firm. Do not use crushed concrete as a fill near an aquatic habitat.

WARNING! CAUSES IRRITATION - Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin, eyes or nasal passages from alkali in Portland cement. When wet, contact with the skin or eyes may result in irritation or burns. FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention. WARNING! HARMFUL IF INHALED - Avoid breathing dust. Keep container closed. Use with adequate ventilation. Excessive exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Crystalline Silica has been classified by IARC and NTP as a carcinogen.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 3-10

www.sakrete.com • 866-SAKRETE 866-725-7383