
## Midwest Tube Mills, Inc.

## MT 15



Midwest Tube Mills MT 15 fence framework is ideally suited for light commercial applications such as parking facilities, parks, playground enclosures and other low security uses. In addition, MT 15 can be used for certain residential applications that require a stronger framework than our standard grade residential pipe or tubing products such as gate framework.

Superior Corrosion Resistance - With our advanced inline coating process, Midwest Tube Mills guarantees the highest degree of corrosion resistance available. MT 15 features the identical coating process of our MT 40 product. This process includes an initial hot dip steel, an intermediate conversion coat and an organic vacuum sealed clear top coat for maximum protection against corrosion. The ID is zinc coated prior to forming.

**Strength -** MT 15 is fabricated to conform with a high yield strength of 50,000 PSI. Its yield strength is 40% greater and 35% lighter than hot dip galvanized pipe.





**Made in U.S.A.** - All MT 15 product from Midwest Tube Mills is manufactured in the USA meeting Buy America(n) requirements.

Available in Polyester and heavy mil Polyolefin Color Coat.

## MT 15 vs. Hot Dip Comparison Chart

Posts		Outside Dimensions (in.)	Pipe Wall Thickness (in.)	Weight (lbs./ft.)	Section Modulus (inches <sup>3</sup> )	Yield Strength (psi)	Bending Moment (lbs. in.)	Bending Strength (lbs.) 4' Cantilever	Bending Strength (lbs.) 6' Cantilever	Bundle Counts
1- <sup>5</sup> /8" <b>0.</b> D.	MT 15 HD	<b>1.660</b> 1.660	<b>0.072</b> 0.110	<b>1.22</b> 1.82	<b>0.1367</b> 0.1948	<b>50,000</b> 25,000	<b>6,835</b> 4,870	<b>142</b> 101	<b>95</b> 68	61
1- <sup>7</sup> /8" <b>0.</b> D.	MT 15 HD	<b>1.900</b> 1.900	<b>0.072</b> 0.110	<b>1.41</b> 2.10	<b>0.1821</b> 0.2618	<b>50,000</b> 25,000	<b>9,104</b> 6,544	<b>190</b> 136	<b>126</b> 91	61
2- <sup>3</sup> /8" <b>0.</b> D	MT 15 HD	<b>2.375</b> 2 <b>.</b> 375	<b>0.072</b> 0.110	<b>1.77</b> 2.66	<b>0.2911</b> 0.4237	<b>50,000</b> 25,000	<b>14,556</b> 10,592	<b>303</b> 221	<b>202</b> 147	37
Top Rail							10' Free Supported			
1- <sup>3</sup> /8" <b>0.D.</b>	MT 15 HD	<b>1.315</b> 1.315	<b>0.072</b> 0.110	<b>0.96</b> 1.42	<b>0.0829</b> 0.1159	<b>50,000</b> 25,000	<b>4,143</b> 2,898	<b>138</b> 97		91
1- <sup>3</sup> /8" <b>0.</b> D.	MT 15 HD	<b>1.660</b> 1.660	<b>0.072</b> 0.110	<b>1.22</b> 1.82	<b>0.1367</b> 0.1948	<b>50,000</b> 25,000	<b>6,835</b> 4,870	<b>228</b> 152		61

